PCT

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(54) Title: RAPIDLY DECORRELATING SPREADING SEQUENCES FOR DS–CDMA TRANSCEIVERS

(57) Abstract

A transmitter for a communication system transmits consecutive chips of a signal shifted in phase +/– 90 degrees +/– an angle between 0 degrees and 45 degrees which is a function of a spreading gain.

RAPIDLY DECORRELATING SPREADING SEQUENCES
FOR DS-CDMA TRANSCEIVERS

Field of the Invention

5

The present invention relates generally to code division multiple access (CDMA) systems, and more particularly to a modulation scheme for gain spreading in a direct sequence CDMA (DS-CDMA) system.

10

Background of the Invention

DS-CDMA or CDMA communication systems are being implemented as cellular telephone systems. A CDMA system
15   includes a system controller and at least one base station. Each base station provides communication service to a fixed geographic area or cell. Mobile stations in a cell communicate with the base station for that cell. Communication with a mobile station is handed off among base stations as the mobile station moves among cells. One example
20   of such a system is a system according to EIA/TIA interim standard 95 Mobile Station-Base Station Compatibility Standard for Dual-Mode Wideband Spread Spectrum Cellular System ("IS-95").

A typical DS-CDMA transmitter 100 is shown in FIG. 1. The transmitter accepts information bits. These may be digitized,
25   compressed voice or digital data formatted in an appropriate protocol. These bits are encoded for error correction and interleaved in encoder and interleaver 101. The resulting binary data stream is mapped from binary data (0,1) to symbols (-1,+1) in the binary-to-numeric block 102. Each symbol of the emerging data stream is
30   multiplied by a length N Walsh code, where N is normally an integer power of 2, by multiplier 103, in a process referred to as Walsh covering. The duration of each element of the Walsh code is referred to as the chip duration and the inverse of this quantity is the chip rate. Because all length N Walsh codes are orthogonal to each other,
35   this will allow the receiver to separate individual uses by correlation to a received signal with the given Walsh code. The sequence formed

1

by the Walsh covering is then multiplied by a complex spreading
sequence.   This is accomplished by performing two real multiplies,
one in which the Walsh covered sequence is multiplied by a first

40   psuedorandom noise sequence PNi by multiplier 104 to form the in-
phase channel and the other by a second sequence PNq in multiplier
105 to form the quadrature component of the complex baseband
signal. Note that the spreading sequence formed by PNi and occupy a
quartenary phase shift keyed (QPSK) constellation, and therefore will

45   be referred to as a QPSK modulation or a QPSK spreading sequence.
In general, a spreading sequence will be considered any sequence
with relatively uniform spectrum over a desired range which is
multiplied by a second sequence for the purpose uniformly
distributing a signal across the extent of the desired band.   For

50   systems such as IS-95, in which offset quartenary phase shift keying
is specified for subscriber unit transmission, the quadrature
component of the complex baseband signal is delayed by 1/2 chip by
delay element 106.   Both the delayed quadrature and the in-phase
component of the signal are then filtered by identical spectral

55   shaping filters 107 and 108 to prevent out-of-band emissions.   The
filtered in-phase component is then multiplied by $\cos(\omega t)$ in
multiplier 108 and the filtered quadrature component by $\sin(\omega t)$ in
multiplier 109 and the resulting signals summed in summer 110 to
up-convert the baseband signal to the desired carrier frequency.

60   The modulated carrier produced by summer 110 is then amplified
by power amplifier 112 to the desired power level.
        When the in-phase and quadrature signals are scaled in filters
107 and 108, the peak magnitude of the output of the in-phase
and/or quadrature signals will exceed the average output magnitude.

65   The ratio of the peak magnitude of the filter output to the average
level is referred to as peak-to-average ratio.   High peak-to-average
ratios are undesirable because the power amplifier 112 must be
linear over the entire signal range, including the peak value.
Therefore the peak signal level determines both the size and bias

70   requirements of the power amplifier.   High peak-to-average ratios
therefore imply higher current drain, large size, and more costly

2

power amplifiers. These characteristics become very important in low cost, battery powered subscriber units.

75   Attempts have been made to reduce the peak-to-average ratio to eliminate the necessity of increasing the capacity of the power amplifier. Focus has been placed mainly upon the signal spreading scheme since certain schemes have been found to directly reduce the peak-to-average ratio. These sequences must be chosen in a manner which not only reduces the peak-to-average ratio but also has a

80   short duration auto-correlation to preserve the interference averaging properties of QPSK spreading.

Accordingly, a need exists for a modulation scheme which minimizes linearity requirements in single code scenarios.

85   Brief Description of the Drawings

FIG. 1 is an overview of a DS-CDMA transmitter.

FIG. 2 is a typical impulse response and frequency response of the spectral shaping filters employed in a DS-CDMA system.

90   FIG 3. is the constellation of a QPSK spreading sequence.

FIG 4. is a representation of the vector addition of two vectors each with 4 possible values.

FIG 5. is a block diagram of a $\pi/2$-BPSK modulator.

FIG 6. is a representation of the possible phase shifts of the

95   proposed spreading sequence.

FIG 7. shows the vector addition of the chip components in a two chip duration filter system under the proposed invention.

FIG 8. is a block diagram of the proposed spreading sequence.

100   Detailed Description of a Preferred Embodiment

The present invention provides a spreading sequence for a communication system which is preferably a DS-CDMA system. Consecutive chips of signals transmitted in the communication

105   system are shifted in phase for spread spectrum modulation. The phase shift is plus or minus (+/-) 90 degrees plus or minus an angle phi having a value between 0 degrees and 45 degrees.

3

In the preferred embodiment of the present invention, phi is a function of the spreading function and is preferably pi/6. The

110 modulation scheme is a QPSK modulation and the angle phi, in a second embodiment, is randomly selected. The spreading sequence is preferably included in a transmitter in the telecommunication system.

The peak signal level of a DS-CDMA transmitter can be

115 determined by examination of the peak level of the complex output filters 107 and 108 in FIG. 1, in which the in-phase filter 107 output forms the real part and the quadrature filter 108 output is forms the imaginary part of the complex signal. Under this assumption and the further assumption that filters 107 and 108 have identical impulse

120 responses, this complex output signal is the convolution of the complex input signal, formed in a like manner to the output signal except for the use of the signals at the input to the filter, and the filter impulse response. A typical impulse response of these filters is shown in FIG. 2. While this is a typical impulse response and not

125 directly used by any known system, several properties of impulse response 201 are common to most DS-CDMA systems which attempt to minimize the bandwidth occupied by the transmitted signal. First, the vast majority of the energy of the filter is contained in the interval +/- Tc, and second the first zero crossings of the filter

130 impulse response 201 occur near the points +/- Tc. The second condition follows because the minimum bandwidth which can be occupied by a DS-CDMA system is given by the chip rate, Rc. A typical frequency response 202 is shown in FIG. 2. Given these two properties, much insight into the techniques affecting the peak signal

135 level of the output complex signals can be investigated by assuming the impulse response of filters 107 and 108 are zero outside of the interval +/- Tc.

For the DS-CDMA system shown in FIG. 1, the input complex

140 signals are constant over a chip duration Tc. Further, this signal can take on the values

$$sqrt(1/2) \ *(+/- \ 1 \ +/- \ j)$$

4

SUBSTITUTE SHEET (RULE 26)

145   where j is the square root of -1 and the term sqrt(1/2) is included to normalize the magnitude of each chip. This is shown graphically in the QPSK constellation shown in FIG. 3. Therefore, with the assumption that impulse response 201 is zero outside of the region +/- Tc, the output complex signal consists of two components, one

150   due to the present chip input and the one due to the previous chip input. The magnitude of the output complex signal will be maximized when these two complex components add with the same phase. In this case the magnitude of the resultant will be twice the magnitude of signal due to each component. For this case the

155   components due to each of the two chips will have equal magnitude and have either the same phase angle or differ in phase by 90, 180, or 270 degrees. Assume that the filter gain is such that the magnitude of these chip components is normalize. This vector addition of the complex valued components is shown in FIG. 4 (400).

160   In 401, the components are shown adding in phase yielding a magnitude of 2, in 402 and 403, the components are +/- 90 degrees out of phase yielding a magnitude sqrt(2), and in 404 the components are 180 degrees out of phase yielding zero magnitude. By simply enumerating these for cases, it can be shown that the

165   magnitude of the output complex signal will either be 0, sqrt(2), or 2. Because the sqrt(2) term appears for two phase differences and all phase differences are equally probable, the average power level in the output complex signal is twice the average power level of each chip component and the peak power level is 4 times the power in

170   each chip component. Therefore the peak-to-average ratio is 2 or 3 dB.

       In the previous situation, the peak signal level occurs when two consecutive chips posses the same value. If this situation is not

175   allowed, the peak-to-average ratio can be reduced. One modulation method which accomplishes this is referred to as $\pi/2$ shifted binary phase shift keying ($\pi/2$-BPSK). With $\pi/2$-BPSK, the phase of the next chip is determined by changing the phase of the present chip by +/- 90 degrees, with the phase selected randomly as shown in FIG. 4

5

SUBSTITUTE SHEET (RULE 26)

180   (400). The Π/2-BPSK system shown in FIG. 4 generates the Walsh
       covered information identically to the system in FIG. 1. The
       spreading sequence is now generated by multiplying j by a PN
       sequence generated by pseudorandomly selecting +/- 1 in multiplier
       402 and multiplying this value by the present value of the chip
185   sequence stored in register 403 in multiplier 404. Register 403 is
       clocked at the chip rate. This generates a sequence in which
       consecutive chips are either +/- 90 degrees out of phase with each
       other.

           For the simple length 2*Tc filter used above, the π/2-BPSK
190   spreading sequence will produce output complex chip components
       which are always either +/- 90 degrees out of phase with each other.
       Therefore, the output complex signal have a constant amplitude
       sqrt(2) times larger than the value of each chip component. The
       peak-to-average ratio is therefore 1 or 0 dB, a 3 dB improvement
195   over QPSK. For more realistic filters, the improvement is not as great
       but still substantial. For a square root raised cosine filter with an
       excess bandwidth factor of 0.2, the peak-to-average ratio is less than
       4.9 dB and 3.0 dB 99 % of the time for QPSK and π/2-BPSK
       respectfully.

200   While π/2-BPSK shows marked improvement in the peak-to-
       average ratio when compared to QPSK, π/2-BPSK shows a carrier
       phase dependence on the level of interference. In a situation in
       which one dominate interferer exists, this situation is undesirable as
       it can lead to long periods of time in which the interference is higher
205   than the average value by as much as 3 dB. For high speed data
       transmission, in which one subscriber unit may transmit with very
       high power levels, it is likely that a dominant interferer will often
       exist.

           To understand the dependence of interference levels on the
210   relative phase of the desired and interfering signal, consider the case
       in which two signals, a desired and an interfering, are received
       coherently at the same base with equal energy. Because of
       differences in the path length from the transmitters to the receiver,
       these two will differ in carrier phase by an angle σ. If these two
215   signals are received with the same phase or antiphased, σ = 0 or 180

6

degrees, the two signals will posses the same energy after coherent detection of the desired signal. If they are received with σ = +/- 90 degrees, none of the interfering will remain after coherent detection of the desired signal. In general, it is well known the coherent

220   detection will cause the interference signal to vary as the cos(σ).

Now add modulation to above discussion of the carrier phase. If the desired and interfering signal are in phase during chip period N, the desired and interfering signals will either be in phase or antiphase during chip period N+1 if π/2-BPSK modulation is

225   employed. This is because both the desired and interfering signals will have changed phase by +/- 90 degrees, causing the relative phase of the two to change by 0 or 180 degrees. Therefore, if the interference is at a maximum due to carrier phase at chip N, it will be at a maximum during chip N+1. By induction, the interference

230   level will always be at a maximum. Note that in practice this situation will not persist indefinitely due to motion of the mobile units and drifting of reference oscillators. However, these changes are slow and the interference can remain strong for considerable periods.

235   For QPSK modulation if carrier phase alignment exists at chip N, the relative phase the desired and interfering signals will differ by 0, 90, 180, or 270 degrees at chip N+1. The interference energy is equally likely to be either 1 or 0, and will on average be 0.5. Therefore, the phase alignment on a given chip implies that the

240   average value of interference will be seen on subsequent chips. Because the relative phase angles of the desired and interfering signals are a function of path length and therefore random, to see the average value of interference regardless of relative carrier phase angle is the most desirable result possible.

245   The proposed invention teaches a spreading modulation which restricts the phase transitions of the input complex signal to +/- (90 + αΦ) degrees, where α is a binary (+/-1) code operating at the chip rate and Φ is a fixed phase term having a value between 0 and 45 degrees. These transitions are shown in FIG. 6 (600). The spreading

250   modulation is applied to the data bits after Walsh covering. One method to generate this modulation is shown in FIG. 7 (700).

7

The proposed modulation shows good but imperfect phase averaging. If the desired and interfering signal are phase aligned on chip N, at chip N+1 the signals will differ in phase by 2Φ, 180, or

255   180-2Φ degrees. In the limiting cases of Φ = 0 degrees, the phases differ only slightly from 0 and 180 degrees, and little decorrelation occurs. As Φ approaches the other limit of 45 degrees, the phase changes approach 0, +/- 90, and 180 degrees, each equally likely, and decorrelation occurs in one chip period. Between these limiting

260   cases, decorrelation will not occur instantly. However, because the effects of the misalignment of carrier phase are cumulative, the interference level does decorrelate. The rate of this decorrelation increases with Φ. Note that the period for interference levels to return to average given that phase alignment occurred on chip N is a

265   function of the conditional auto-correlation of the spreading sequence. As the auto-correlation given that phase alignment occurred on chip N becomes shorter, the time for interference levels to return to normal will become shorter as well.

The proposed modulation decreases the peak-to-average ratio

270   by guaranteeing that consecutive chips cannot line up in phase. This modulation does not give orthogonal output chip components as with π/2-BPSK, but can come arbitrarily close with small Φ. Assume that the two chip components 701 and 702 are both unit magnitude. Then the maximum of the resultant will have a magnitude of

275    $$sqrt(2*(1+sin(Φ)))$$
and the minimum will be
$$sqrt((2*(1-sin(Φ)))$$
The average energy will be the average of the square of the above two equations, or simply 2. The peak-to-average of the energy is

280   therefore 1+sin(Φ) for the simple two chip duration filter. FIG. 8 gives actual peak-to-average ratios and decorrelation periods for a square root raised cosine filter with an excess bandwidth factor of 0.2. The peak-to-average ratio given is the value which is not exceeded 99% of the time. The decorrelation periods are given in

285   chip periods, Tc. This defines the minimum appropriate spreading gain as a sequence which decorrelates in less than a bit time. Decorrelation in less than a bit time is important because sequences

8

which do not decorrelate in less than a bit can have significant
variations in interference levels from one bit to the next which
290   results in a higher bit error rate than would be observed in average
interference levels are observed over all bits.

Φ	Peak to Average Ratio (dB)	Suitable Spreading factors
π/32	3.0	>=64
2π/32	3.2	>=16
3π/32	3.4	>=8
4π/32	3.6	>=4
π/4 (equivalent to π/4 QPSK)	4.5	Any
QPSK	4.9	Any
O-QPSK	4.2	Any

Summarizing, the proposed spreading sequence is for a DS-
295   CDMA radio transmitter. The phase consecutive chips of the
transmitted signals are shifted plus or minus 90 degrees plus or
minus an angle between 0 degrees and 45 degrees.   The spreading is
accomplished by multiplying a sequence of modulated information
bits by the spreading sequence.   The angle of the shift of the
300   spreading sequence may be chosen in response to pairs of bits from
pseudorandom number generators as shown in FIG 8.   This angle Φ
may be set to any value.   However, Φ may be varied as a function of
spreading gain to allow the minimum peak-to-average ratio to be
achieved while still keeping the conditional cross correlation of time
305   shifted versions of this spreading sequences short relative to a bit
time. Also note that a value of Φ of 30 degrees gives a special case in
which the constellation contains only 6 possible points, 4 of which
will be used at any one time.
What is claimed is:

310

9

CLAIMS:

1. A spreading sequence for a transmitter in a communication system where a phase of consecutive chips of signals to be
315   transmitted are shifted +/- 90 degrees +/- an angle between 0 degrees and 45 degrees.

2. A spreading sequence according to claim 1 wherein the spreading sequence is a spread spectrum modulation scheme.
320

3. A spreading sequence according to claim 1 wherein the angle is pi/6 radians, is a function of a spreading gain or is randomly selected.

325   4. A spreading sequence according to claim 1 wherein the communication system is a CDMA system.

5. A method of spreading signals in a transmitter in a communication system comprising the steps of:
330   selecting an angle between 0 and 45 degrees;
                    phase shifting consecutive chips of the signals by +/- 90 degrees +/- the angle; and
                    transmitting the signals.

335   6. A method according to claim 5 wherein the step of selecting an angle comprises randomly selecting an angle for each new one of the consecutive chips.

7. A method according to claim 5 wherein the step of
340   transmitting the signals comprises transmitting the signals in a CDMA system.

10

8. A transmitter for a communication system comprising a modulator which, when operatively coupled to the telecommunication system, phase shifts consecutive chips of signals
345   +/- 90 degrees +/- an angle between 0 and 45 degrees for transmission.

9. A transmitter according to claim 8 wherein the modulator comprises a means for phase shifting the consecutive chips.
350
10. A transmitter according to claim 8 wherein the modulator uses a QPSK modulation scheme.

1 1

FIG.1

— PRIOR ART —

FIG.2

— PRIOR ART —

FIG.3

— PRIOR ART —

FIG.4

— PRIOR ART —

FIG.5

3 / 3

FIG.6

600

x - PRESENT VALUE
o - POSSIBLE NEXT VALUES

FIG.7

FIG.8

800

— PRIOR ART —

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/10534

A. CLASSIFICATION OF SUBJECT MATTER
IPC(6) :H04B 15/00, 7/216; H04K 1/00; H04L 27/30
US CL   : 375/200, 201, 206; 370/335, 209, 342
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. :   375/200, 201, 206; 370/335

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS, MAYA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,619,524 A (Ling et al.) 09 April 1997 (09.04.97), cols. 5-10.	1-5,7-10
---		------------
Y		3,6
Y	US 4,652,838 A (Nossen) 24 March 1987 (24.03.87), cols. Fig 4. and col. 4, lines 8-37.	3, 6
A	US 5,623,485 A (Bi) 22 April 1997 (22.04.97).	1-10
A	US 5,581,575 A (Zehavi et al.) 03 December 1996 (03.13.96).	1-10

☐ Further documents are listed in the continuation of Box C.   ☐ See patent family annex.

*	Special categories of cited documents:	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A"	document defining the general state of the art which is not considered to be of particular relevance		
"E"	earlier document published on or after the international filing date	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means		
"P"	document published prior to the international filing date but later than the priority date claimed	"&"	document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
02 SEPTEMBER 1998	**19 OCT 1998**

Name and mailing address of the ISA/US	Authorized officer
Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231	MICHAEL W. MADDOX *Diane Smith for*
Facsimile No. (703) 305-3230	Telephone No. (703) 308-9557

Form PCT/ISA/210 (second sheet)(July 1992)★